SB-1S,SB-1F

Plain | Flap | **Ball** | Spinner
Stainless | Mica plate | Protective wire mesh | With protective cover

SB-1S

■Features

1. Flowing state of fluid can be checked with the movement of the balls inside the sight glass.
2. Compact, lightweight and space saving.
3. Can be connected to horizontal/vertical piping (but glass part should face sideways).

SB-1F

■Specifications

Model		SB-1S	SB-1F
Application		Cold and hot water	
Maximum working pressure		1.0 MPa	
Max. temperature		85°C	
Material	Body	Ductile cast iron	
	Glass	Hardened glass	
	Ball	Synthetic resin	
Connection		JIS Rc screwed	JIS 10K FF flanged

· Glass part and balls are consumable parts.

■Dimensions (mm) and Weights (kg)

· SB-1S

Nominal size	d	L	W	Weight
15A	Rc 1/2	80	35	0.7
20A	Rc 3/4	90	35	0.8
25A	Rc 1	115	44	1.4
32A	Rc 1-1/4	127	57	2.5
40A	Rc 1-1/2	140	57	2.8
50A	Rc 2	162	73	5.4

· SB-1F

Nominal size	d	L	W	Weight
15A	15	130	35	2.2
20A	20	130	35	2.6
25A	25	150	44	4.1
32A	32	160	57	5.9
40A	40	170	57	6.2
50A	50	200	73	9.5



SB-1S



SB-1F